

**Data Sheet** 

# Industrial White, ABS-like

#### **Alternative Designations**

**Key Features** 

Accura Xtreme White 200

Stiff, durable • High impact strength • Low viscosity Good moisture resistance

## Description

Xtreme White 200 is a type of engineering thermoplastic that is frequently used in the production of durable and strong plastic parts. This material is known for its resistance to impact, heat, and chemicals. Because of its many benefits, Xtreme White 200 is often used as an alternative to ABS plastic. Its applications include everything from medical devices to automotive parts. It offers a stunning white finish with clean sidewall quality. It is applied in general purpose prototyping and snap fits.

#### **Mechanical Properties**

### **Thermal Properties**

<del>-</del>		
Tensile modulus	2300 – 2630 MPa	Heat deflection temperature (
Tensile strength	45 – 50 MPa	Heat deflection temperature (
Elongation at break	7 – 20%	
Flexural strength	75 – 79 MPa	
Flexural modulus	2.35 – 2.55 GPa	
Hardness (Shore D)	78 – 80	

Heat deflection temperature (1.80 MPa)	42°C
Heat deflection temperature (0.45 MPa)	47°C

## **Physical Properties**

Density	1.12 g/cm <sup>3</sup>
---------	------------------------

#### Reference

Datasheets provided by Xometry contain materials sourced through trusted OEMs, material distributors, and databases. Please visit Materialdatacenter.com for further information on this material.